

ARENA ASSEMBLY GUIDE 2019





2/20/2019





























•Executive Committee

- Jafar Chegini,Iran (2nd Term) (Exec 2018-2021)
- Sören Schwertfeger, Germany/China (1st Term) (Exec 2016-2019)
- Tetsuya Kimura, Nagaoka Univ. of Technology, Japan (1st Term) (Exec 2016-2019)
- Raymond Sheh, Australia (2nd Term) (Exec 2017-2020)

•Technical Committee

- Mehdi Dadvar (TC 2016-2019)
- Raimund Edlinger (TC 2016-2019)
- Masayuki Okugawa, Japan (TC 2019-2021)
- Sakol Nakdhamabhorn (TC 2016-2019)

•Organizing Committee

- Local Chair: Raymond Sheh
- Adam Jacoff (NIST, USA)
- Ann Virts (NIST, USA)
- Kenny Kimble
- Kam Saidi
- Johannes Pellenz (BAAINBw, Germany)
- Ehsan Mihankhah (Singapore)
- Xieyuanli Chen



ASTM International Committee on Homeland Security Applications; Response Robots (E54.09)




Acknowledgements


This work was sponsored by Philip Mattson and Kai-Dee Chu from the Department of Homeland Security, Science and Technology Directorate, Capability Development Support Group, Office of Standards through an interagency agreement with the National Institute of Standards and Technology.

Dozens of people have contributed to the development and validation of these test methods. They include FEMA urban search and rescue task force teams, firefighters, law enforcement, collaborating test facilities, other civilian and military organizations, and commercial manufacturers.

Disclaimer

Commercial equipment shown in this document are for illustrative purposes only. This does not imply recommendation or endorsement by the National Institute of Standards and Technology, nor does it imply that the products identified are necessarily the best available for the purpose.






ASTM International Committee on Homeland Security Applications; Response Robots (E54.09)



Containment – Trays (11 bays (6 trays per bay))




PURCHASE LIST:

- ☐ [66] 1200 x 2400 x 15 mm OSB
- ☐ [77] 45 x 70 x 2400 mm post

CUT LIST:


- ☐ [66] 1200 x 2400 x 15 mm OSB (A)
- ☐ [44] 45 x 90 x 2400 Post **(B)**
- ☐ [44] 45 x 90 x 1200 Post (C)
- ☐ [44] 45 x 90 x 600 Post (D)



Note: Post D is centered on Panel 1 Region Management 1 Panel 1 (22)

Fabrication

- There are 3 "types" of floor panels
- Attach post: B/C/D on edge to panel A as shown in **Figure B, C, D**.
- Note: Post D is centered on Panel 1
- Note: Post D on Panel 3 is 600 mm from edge.



Panel 2 (22)





FIGURE D


Panel 3 (22)

ASTM International Committee on Homeland Security Applications; Response Robots (E54.09)



Containment – Walls (4 bays)





PURCHASE LIST:


- ☐ [24] 1200 x 2400 x 15 mm OSB
- ☐ [36] 45 x 90 x 2400 mm Post
- ☐ [2] 90 x 90 x 2400 mm Post


CUT LIST:

- ☐ [12] 600 x 1140 x 15 mm short wall (A)
- ☐ [20] 600 x 2400 x 15 mm long wall **(B)**
- ☐ [4] 1200 x 2400 x 15 mm long wall (op) (C)
- [4] 1140 x 2400 x 15 mm short wall (op) (D)
- ☐ [4] 600 x 1100 x 15 mm desk top (E)
- ☐ [8] 45 x 90 x 300 mm Post (F)
- ☐ [8] 45 x 90 x 510 mm Post (G)
- ☐ [24] 45 x 90 x 600 mm Post (H)
- ☐ [8] 45 x 90 x 1100 mm Post (I)
- ☐ [4] 45 x 90 x 1400 mm Post (J) 45° Mitre

cut long to long point

- ☐ [16] 45 x 90 x 2400 mm Post (K)
- ☐ [4] 90 x 90 x 1000 mm Post 45 (L)






Fabrication


- Attach wall panels and posts as shown in Figure A/B/C.
- NOTE: Post H should be attached to Panel A before attaching to Panel B.
- Attach bracing as shown in Figure A/B/C
- Fabricate desk top as shown in Figure D and place as shown in Figure A.

ASTM International Committee on Homeland Security Applications; Response Robots (E54.09)



Containment – Walls (7 bays)







PURCHASE LIST:

- ☐ [72] 1200 x 2400 x 15 mm OSB
- ☐ [112] 45 x 90 x 2400 mm Post
- ☐ [4] 90 x 90 x 2400 mm Post

CUT LIST:

- ☐ [21] 1200 x 1140 x 15 mm short wall (A)
- ☐ [35] 1200 x 2400 x 15 mm long wall (B)
- ☐ [7] 1200 x 2400 x 15 mm long wall op (C)
- ☐ [7] 1140 x 2400 x 15 mm short wall op (D)
- ☐ [7] 600 x 1100 x 15 mm desk top (E)
- ☐ [14] 45 x 90 x 300 mm Post (**F**)
- ☐ [14] 45 x 90 x 510 mm Post (G)
- ☐ [28] 45 x 90 x 1200 mm Post (H)
- ☐ [14] 45 x 90 x 1100 mm Post (I)
- ☐ [7] 45 x 90 x 1400 mm Post (**J**) 45° Mitre
- cut long to long point
- ☐ [70] 45 x 90 x 2400 mm Post **(K)**
- ☐ [7] **90 x 90** x 1000 mm Post 45 **(L)**





Fabrication

- Attach wall panels and posts as shown in Figure A/B/C.
- NOTE: Post H should be attached to Panel A before attaching to Panel B.
- NOTE: Post F and K (on the horizonal wall) should be attached before vertical post K.
- Attach bracing as shown in Figure A/B/C
- Fabricate desk top as shown in Figure D and place as shown in Figure A.



ASTM International Committee on Homeland Security Applications; Response Robots (E54.09)



Operator Booth (9)





PURCHASE LIST:

- ☐ [56] 1200 x 2400 x 15 mm OSB
- ☐ [68] 45 x 90 x 2400 in post

CUT LIST:

- ☐ [18] 1200 x 2400 x 15 mm Wall Panel Side(A)
- [9] 1140 x 2400 x 15 mm Wall Panel Back (B)
- ☐ [18] 45 x 90 x 2400 mm Post (C)
- [9] 600 x 1100 x 15 mm Shelf (D)
- ☐ [9] 45 x 90 x 1100 mm Brace (E)
- ☐ [18] 45 x 90 x 1100 mm Shelf Support Long (F)
- ☐ [18] 45 x 90 x 510 mm Shelf Support (G)





140 mm 2400 mm

Fabrication

- Attach OSB panels A, B shown in Figure A.
- Attach cross brace as shown in Figure A.
- Lay out two Shelf support long (F) 510 mm from each other such that post are on edge. Attach Shelf support short (G) to stud plates as shown in Figure B. Attach OSB panel (D) to stud frame.
- Install shelf unit into operator station. Shelf height is 1000 mm from floor as shown in Figure C.

FIGURE C

ASTM International Committee on Homeland Security Applications; Response Robots (E54.09)




Ramps - 220

PURCHASE LIST:

- [62] 1200 x 2400 x 19 mm OSB
- [46] 90 x 90 x 2400 mm in post



- [220] 550 x 565 x 19 mm OSB (top) (A)
- ☐ [220] 140 x 550 x 19 mm OSB (back) (B)
- ☐ [440] 140 x 530 x 19 mm OSB triangle (sides) (C)
- ☐ [440] 90 x 90 x 140 mm Post 15° Mitre cut sq. to long point (back legs) (D)
- [440] 90 x 90 x 60 mm Post 15° Mitre cut sq. to long point (front legs) (E)






FIGURE A

Ramp Fabrication

- Place triangles (C) flatly on the floor. Attach one top post (E) to support triangle (C) and repeat for additional side as shown in Figure A. Note: Posts will be flush with the top of support triangle (C).
- Attach Front Leg (E) as shown in Figure A.
- Attach ramp surface (A) to support triangles (C). Note: Use rougher side up as the ramp surface if there is a difference in surface texture.
- Attach back plate (B) to high side of ramp as shown in Figure A.

ASTM International Committee on Homeland Security Applications; Response Robots (E54.09)



Tall Ramps - 4




PURCHASE LIST:

- ☐ [3] 1200 x 2400 x 19 mm OSB
- ☐ [3] 90 x 90 x 2400 mm in post

CUT LIST:

- [4] 550 x 565 x 19 mm OSB (top) (A)
- ☐ [4] 550 x 380 x 19 mm OSB (back) (B)
- ☐ [8] 380 x 530 x 220 x 19 mm OSB triangle (sides) (C)
- ☐ [4] 235 x 512 x 19 mm OSB (front) (D)
- \square [8] 90 x 90 x 380 mm Post 15° Mitre cut sq. to long point (back legs) (E)
- □ [8] 90 x 90 x 260 mm Post 15° Mitre cut sq. to long point (front legs) (F)



550 mm E C E B D

Ramp Fabrication

- Cut out (8) sides as shown in **Figure A.**
- Attach back plate C to Post E as shown in Figure A.
- Attach side B to Post E as shown in Figure B
- Attach post F as shown in Figure
 B . Repeat for additional side.
 NOTE: Inset post F by 25mm (1 in).
- Attach front plate D to post F as shown in Figure B.
- Attach ramp surface (A). Note: Use rougher side up as the ramp surface if there is a difference in surface texture.






ASTM International Committee on Homeland Security Applications; Response Robots (E54.09)



Maze Wood



PURCHASE LIST:

- ☐ [75] 1200 x 2400 x 11 or 15 mm OSB
- ☐ [147] 45 x 90 x 2400 mm in post

CUT LIST:

- ☐ [75] 1140 x 2400 x 11 or 15 mm OSB
- ☐ [18] 45 x 90 x 2400 mm Post (Green)
- ☐ [24] 45 x 90 x 2280 mm Post (Orange)
- ☐ [57] 45 x 90 x 2100 mm Post (Green)
- ☐ [48] 45 x 90 x 1100 mm Post (Black)

Cut down maze walls KEEP scrap wood for padding.






ASTM International Committee on Homeland Security Applications; Response Robots (E54.09)



Victim Fidcials (40 halves)





PURCHASE LIST:

- ☐ [20] 45 x 90 x 2400 mm in post
- ☐ [20] 600 ID x 1200 mm Concrete Form

CUT LIST:

- ☐ [80] 45 x 90 x 600 mm Post (A)
- ☐ [20] 600 ID x 1200 mm Concrete Form (B)





Fabrication

FABRICATION INSTRUCTIONS – Barrels

Cut concrete form in half lengthwise

FABRICATION INSTRUCTIONS – Barrel Braces

 Drill 1/4 in thru hole centered in barrel braces as shown in Figure A. Repeat for additional 39.

FABRICATION INSTRUCTIONS – Barrel halves

Attach braces as shown in Figure B. Repeat for additional 39 halves.


FIGURE A



ASTM International Committee on Homeland Security Applications; Response Robots (E54.09)




Doors



PURCHASE LIST:

- ☐ [1] Right Hung Door
- ☐ [1] <u>Left</u> Hung Door
- ☐ [12] 45 x 250 x 2500 mm post
- ☐ [4] 45 x 90 x 2400 mm post
- ☐ [4] Lever style handles
- ☐ [2] Door Closers

https://www.amazon.com/ryobi-doorman-door-closer-dm85d/dp/b0053xz1o4)





Fabrication


Fabrication on-site



ASTM International Committee on Homeland Security Applications; Response Robots (E54.09)



Curbs



PURCHASE LIST:

- ☐ [4] 1200 x 2400 x 15 mm OSB
- ☐ [2] 90 x 90 x 2400 mm Post

CUT LIST:

- ☐ [2] 1100 x 2200 x 15 mm OSB (A)
- ☐ [2] 1100 x 2400 x 15 mm OSB (B)
- ☐ [2] 90 x 90 x 1510 mm Post (C) 45° Mitre cut long to short point


FIGURE A

☐ [2] 90 x 90 x 1100 mm Post (**D**)

1510 mm

Fabrication

- Cut (2) post C as shown in Figure A.
- Attach OSB Panels A/B to Posts C/D as shown in Figure B.






ASTM International Committee on Homeland Security Applications; Response Robots (E54.09)



Crossover Ramps




PURCHASE LIST:

☐ [2] 45 x 90 x 2400 mm post

CUT LIST:

- ☐ [4] 45 x 90 x 1100 post (A)
- ☐ [32] ramps from Pg. 9 **(B)**



Fabrication

- Arrange ramps B as shown in Figure
 A.
- Add spacer as shown in **Figure A.** spacer.


FIGURE A



ASTM International Committee on Homeland Security Applications; Response Robots (E54.09)



Raised Ramps




PURCHASE LIST:

☐ [2] 45 x 90 x 2400 mm post

CUT LIST:

- ☐ [4] 45 x 90 x 1100 post (A)
- ☐ [28] ramps from Pg. 9 (B)
- ☐ [4] ramps from Pg. 10 (C)



Fabrication

- Arrange ramps B and C as shown in Figure A.
- Add spacer as shown in Figure A.

FIGURE A


National Institute of Standards and Technology U.S. Department of Commerce

Standard Test Methods for Ground Systems

ASTM International Committee on Homeland Security Applications; Response Robots (E54.09)



Rails




PURCHASE LIST:

- ☐ [2] 1200 x 2400 x 15 mm OSB
- ☐ [10] 45 x 90 x 2400 mm in post
- ☐ [4] 90 x 90 x 2400 mm in post
- ☐ [8] 90 mm angle brackets

CUT LIST:

- ☐ [2] 1100 x 2200 x 19 mm OSB (A)
- ☐ [4] 45 x 90 x 2200 mm in post (B)
- ☐ [12] 45 x 90 x 1010 mm in post (C)
- ☐ [4] 90 x 90 x 2400 mm in post (D)






FIGURE A

Fabrication

- Lay out two post (B) 1100mm from each other such that post are on edge. Attach post (C) to post as shown in **Figure A**. Repeat for 1 additional frame.
- Attach (1) OSB panel (A) to frame. Repeat for one additional panel as shown in **Figure A**.
- Attach post (D) using angle brackets.
 Repeat for 3 additional posts.




FIGURE B



ASTM International Committee on Homeland Security Applications; Response Robots (E54.09)




Slalom Walls


PURCHASE LIST:

- ☐ [2] 1200 x 2400 x 15 mm OSB
- ☐ [1] 90 x 90 x 2400 mm Post
- ☐ [1] 45 x 90 x 2400 mm Post

CUT LIST:

- ☐ [4] 1100 x 1200 x 15 mm OSB (A)
- ☐ [2] 90 x 90 x 600 mm Post (B)
- ☐ [4] 45 x 90 x 600 mm Post **45° Mitre cut long to long point (C)**





Fabrication

- Assemble slalom walls as shown in Figure A.
- Add brace C to walls for support.




FIGURE A




ASTM International Committee on Homeland Security Applications; Response Robots (E54.09)



Hurdles





- ☐ [32] 45 x 90 x 2400 mm post
- ☐ [5] 100 mm OD PVC X 2400 mm

CUT LIST:

- ☐ [6] 1100 X 2200 x 15 mm OSB (A)
- ☐ [12] 45 x 90 x 2200 mm Post (B)
- ☐ [36] 45 x 90 x 1010 mm Post (C)
- ☐ [4] 45 x 90 x 200 mm Post (D)
- ☐ [4] 45 x 90 x 300 mm Post (E)
- ☐ [6] 100 mm OD PVC 1100 mm (F)

Floor Panel - QTY 6




FIGURE A




FIGURE B

Fabrication


- Lay out two post (B) 1100mm from each other such that post are on edge. Attach post (C) to post as shown in Repeat for 5 additional frame.
- Attach (1) OSB panel (A) to frame.
 Repeat for nine additional panel as shown in Figure A. Repeat for 5 additional frame.
- Attach brackets fabricated in Figure
 B to sidewall of apparatus.



Standard Test Methods for Ground SystemsASTM International Committee on Homeland Security Applications; Response Robots (E54.09)



Stepfields



PURCHASE LIST:

☐ [90] 90 x 90 x 2400 mm Post

☐ [15] 45 x 90 x 2400 mm Post

CUT LIST:

	Lumber (mm)	Height (mm)	Count
2S	90 x 90 x	90	84
2	90 x 90 x	180	168
3	90 x 90 x	270	176
4	90 x 90 x	360	184
5	90 x 90 x	450	96
4L	45 x 90 x	360	24
9	45 x 90 x	810	4
11	45 x 90 x	990	4
13	45 x 90 x	1170	4
17	45 x 90 x	1530	4
19	45 x 90 x	1710	4

					15	15	13	13	11	11	9	9	
		19	17	17							25	25	
									25	25	2	2	
							~	26	2	2	3	3	l
ı							25	25	2	2	3	3	l
ı					25	25	2	2	3	3	4	4	ı
ı					2.3	23	2	2	3	3	4	4	ı
ı			25	25	2	2	3	3	4	4			ı
ı					2	2	3	3	4	4	5	5	ı
ı	25	25	2	2	3	3	4	4	5	5	4	4	ı
ı	Δ	23	2	2	3	3	4	4			4	4	ı
ı	2	2	3	3	4	4			4	4	3	3	ı
ı	2	2	3	3	4	4	5	5	4	4	3	3	ı
ı	3	3	4	4	5	5	4	4	3	3	2	2	ı
1	3	3	4	4			4	4	3	3	2	2	
ı	4	4	5	5	4 4 4 4		3	3	2	2	25	25	
	4	4	5	5			3	3	2	2	23	2.3	L
ı	5		4	4	3	3	2	2	25	25			ı
1	5	5	4	4	3	3	2	2	23	23	4		
ı	4	4	3	3	2	2	25	25			-	*	ĺ
1							43	4.5					г

	Lumber (mm)	Height (mm)	Count
25	90 x 90 x	90	84
2	90 x 90 x	180	168
3	90 x 90 x	270	176
4	90 x 90 x	360	184
5	90 x 90 x	450	96
4L	45 x 90 x	360	24
9	45 x 90 x	810	4
11	45 x 90 x	990	4
13	45 x 90 x	1170	4
17	45 x 90 x	1530	4
19	45 x 90 x	1710	4

_	3	4	4		3	4	4	3	3	2	2												
Ц	4	5	5	4	4	3	3	2	2	25	25												
4	4	5	5	4	4	3	3	2	2					_			_						
	5	4	4	3	3	2	2	25	25			25	25 2	25	25	2	2	3	3	4	4		
	5	4	4	3	3	2	2	2		4	4					2	2	3	3	4	4	5	5
	4	3	3	2	2	25	25				-	25	25	2	2	3	3	4	4			4	4
	4	3	3	2	2	**	2.3	4L				2.7		2	2	3	3	4	4	5		4	4
	3	2	2	25	~			41	4L	_	~	2	2	3	3	4	4			4	4	3	3
	3	2	2	25	25					25	25	2	2	3	3	4	4	5		4	4	3	3
2	2					4				2	2	3	3	4	4	5	5	4	4	3	3	2	2
2	2	25	25					25	25	2	2	3	3	4	4	5	5	4	4	3	3	2	2
ī				4L	4			2	2	3	3	4	4	5	5	4	4	3	3	2	2	_	
S	25					25	25	2	2	3	3	4	4	5	5	4	4	3	3	2	2	25	25
	_	4L	4L			2	2	3	3	4	4	5	5	_		3	7	2	2	_	-	_	_
				25	25	2	2	3	3		4	5	5	4	4	3	3	2	2	25	25	4	
		_	-	2	2	3	3	4	4	5	5	4	á	3	3	2	2						4L
		25	25	2	2	3	3	4	4	5	5	4	ā	3	3	2	2	25	25	4L			
-	_	2	2	3	3	4	4	5	5	4	4	3	3	2	2	-	-	_	_		4	25	-
S	25	2	2	3	_		4	5	5	4	i à	3	3	2	2	25	25						25
-	_				3	4		_		3	_	_	_	4	4	_	_	4L		_		_	
=	2	3	3	4	4	5	5	4	4		3	2	2	25	25					25	25	2	2
	2	3	3	4	4	5	5	4	4	3	3	2	2			4	4	_	_	_	_	2	2
Ц	3	4	4	5	5	4	4	3	3	2	2	25	25					25	25	2	2	3	3
_	3	4	4	5	5	4	4	3	3	2	2			4L		_		_	_	2	2	3	3
Ц	4	5	5	4	4	3	3	2	2	25	25					25	25	2	2	3	3	4	4
ı	4	5	5	4	4	3	3	2	2	_	_	4L				_	_	2	2	3	3	4	4
,		4	4	3	3	2	2	25	5 25 2		25			25	25	2	2	3	3	4	4		
i	5	4	4	3	3	2	2	2.5	2.7	25	-			2.7	2.7	2	2	3	3	4	4		
												25	25	2	2	3	3	4	4			4	4
														2	2	3	3	4	4	5	5	4	4
												2	2	3	3	4	4	5	5	4	4	3	3
												2	2	3	3	4	4	5	5	4	4	3	3
												3	3	4	4	5	5	4	4	3	3	2	2
												3	3	4	4	5	5	4	4	3	3	2	2
												4	4	5	5	4	4	3	3	2	2	25	25
												4	4	5	5	4	4	3	3	2	2		
												5	5	4	4	3	3	2	2	25	25		
												5	5	4	4	3	3	2	2				
												4	4	3	3	2	2	25	25				
												4	4	3	3	2	2						
												3	3	2	2	25	25						
												3	3	2	2								
												2	2	25	25								
												2	2										
												25	25	25									
																							19
																			15	17	17		
																13	13	15	15				
														11	11								




ASTM International Committee on Homeland Security Applications; Response Robots (E54.09)



ASTM E2804
Mobility: Confined Area Obstacles

Stairs/Landings – 40/45 degree



PURCHASE LIST (Landing):

- ☐ [10] 1200 x 2400 x 15 mm OSB
- ☐ [8] 90 x 90 x 2400 mm Post
- ☐ [20] 45 x 90 x 2400 mm Post

CUT LIST (Landing):

- [4] 1070 x 1070 x 15 mm OSB (A)
- [8] 900 x 1070 x 15 mm OSB (B)
- □ [8] 900 x 1070 x 15 mm OSB (C)
- ☐ [16] 90 x 90 x 895 mm Post (D)
- ☐ [16] 45 x 90 x 980 mm Post (E)
- ☐ [24] 45 x 90 x 1070 mm Post (F)

PURCHASE LIST (Stair):

- [2] 1200 x 2400 x 15 mm OSB
- [6] 50 x 300 x 3600 mm Post
- [5] 25 x 3240 x 1100 mm Bull nosed stair tread **40°**
- [5] 25 x 2740 x 1100 mm Bull nosed stair tread **45°**
- [7] 45 x 90 x 2400 mm Post

CUT LIST (Stair):

- [10] 175 x 1100 x 15 mm OSB (H)
- [2] 900 x 1100 x 15 mm OSB (I)
- \Box [3] 45 x 90 x 780 mm (J) $\underline{40^{\circ}}$ Mitre cut sq. to long pt
- \square [3] 45 x 90 x 690 mm (K) $\underline{40^{\circ}}$ Mitre cut sq. to long pt
- \Box [3] 45 x 90 x 780 mm (L) $\underline{45^{\circ}}$ Mitre cut sq. to long pt
- ☐ [3] 45 x 90 x 555 mm (M) 45° Mitre cut sq. to long pt
- ☐ [2] 45 x 90 x 1100 mm Post (N)
- ☐ [6] 50 x 300 x 3600 mm Post (O) (cut as shown in Fig A)
- ☐ [5] 25 x 2740 x 1100 mm Bull nosed stair tread 40° (P)
- ☐ [5] 1 45 x 90 x 2400 mm Bull nosed stair tread 45° (Q)




FIGURE A






FIGURE B





Fabrication

- Lay out two post (G) 1100mm from each other such that post are on edge. Attach post (E) to post as shown in **Figure A**. Repeat for 3 additional panels.
- Place fabricated panel OSB side down and toe nail the legs (D) into the panel as shown in Figure B.
 Repeat for 3 additional panels.
- Attach cross bracing (F/G) as shown in Figure B. Repeat for 3 additional panels.
- Attach OSB (B/C) to the cube as shown in Figure C. Repeat for 3 additional cubes.

ASTM International Committee on Homeland Security Applications; Response Robots (E54.09)




ASTM E2804 Mobility: Confined Area Obstacles

Stairs/Landings 40°

Fabrication 40°

- Layout stringer (O) as shown in **Figure A.** Repeat for additional two stringers.
- Attach bracing (J K N) as shown Figure B.
- Attach kickplates(H) and stair treads (P) as shown in Figure C.
- Attach back plate (I) as shown in Figure D.



ASTM International Committee on Homeland Security Applications; Response Robots (E54.09)




ASTM E2804 Mobility: Confined Area Obstacles

Stairs/Landings 45°

Fabrication 45°

- Layout stringer (O) as shown in Figure A. Repeat for additional two stringers.
- Attach bracing (L, M N) as shown Figure B.
- Attach kickplates (H) and stair treads (P) as shown in Figure C.
- Attach back plate (I) as shown in Figure D.






ASTM International Committee on Homeland Security Applications; Response Robots (E54.09)



ASTM E2803 Mobility: Confined Area Obstacles



Incline 15 degree

PURCHASE LIST (Landing):

- [3] 1200 x 2400 x 15 mm OSB
- [2] 90 x 90 x 2400 in Post
- [4] 45 x 90 x 2400 in Post

CUT LIST (Landing):

- [2] 1070 x 1070 x 15 mm OSB (A)
- [8] 480 x 1070 x 15 mm OSB (B)
- [4] 45 x 90 x 980 mm Post (C)
- [4] 45 x 90 x 1070 mm Post (D)
- [8] 90 x 90 x 480 mm Post (E)

PURCHASE LIST (Ramp):

- [5] 1200 x 2400 x 15 mm OSB
- [15] 45 x 90 x 2400 mm Post

CUT LIST (Ramp):

- [2] 1100 x 2200 x 15 mm OSB (G)
- [2] 1100 x 2200 x 15 mm OSB (H)
- [1] 450 x 2200 x 15 mm OSB (I)
- [4] 45 x 90 x 300 mm Post (J)
- [4] 45 x 90 x 550 mm Post (K) 15° Mitre cut sq. to long pt
- [2] 45 x 90 x 1100 mm Post (L)
- [4] 45 x 90 x 1750 mm Post (M)
- [8] 45 x 90 x 2150 mm Post (N) 75° Mitre cut sq. to long pt




FIGURE A





FIGURE B






FIGURE C

Fabrication

- Lay out two post (E) 1070 mm from each other such that post are on edge. Attach post (D) to post as shown in Figure A. Repeat for 1 additional panel.
- Place fabricated panel OSB side down and toe nail the legs (F) into the panel as shown in Figure B. Repeat for 1 additional panel.
- Attach cross bracing (D/E) as shown in Figure B. Repeat for 1 additional panel.
- Attach OSB (B/C) to the cube as shown in Figure C. Repeat for 1 additional cube.



National Institute of Standards and Technology U.S. Department of Commerce

Standard Test Methods for Ground Systems

ASTM International Committee on Homeland Security Applications; Response Robots (E54.09)



ASTM E2803 Mobility: Confined Area Obstacles

Incline 15 degree

Fabrication

- Assemble the frame as shown in Figure D. Repeat for additional frame.
- Attach back panel (H) and Attach ramp sub-face (G) as shown in Figure E. Note orientation of panel.
- Attach ramp face (G) and mark path as shown in Figure F. Note orientation of panel.
- Place ramps and deck as shown in Figure G. Note additional bracing may be needed to prevent movement.

CUT LIST (Ramp):

- [2] 1100 x 2200 x 15 mm OSB (G)
- [2] 1100 x 2200 x 15 mm OSB (H)
- ☐ [1] 450 x 2200 x 15 mm OSB (I)
- ☐ [4] 45 x 90 x 300 mm Post (J)
- \Box [4] 45 x 90 x 550 mm Post (K) 15° Mitre cut sq. to long pt
- ☐ [2] 45 x 90 x 1100 mm Post (L)
- ☐ [4] 45 x 90 x 1750 mm Post (M)
- [8] 45 x 90 x 2150 mm Post (N) 75° Mitre cut sq. to long pt







FIGURE D






FIGURE F




FIGURE G




ASTM International Committee on Homeland Security Applications; Response Robots (E54.09)



ASTM E2991/E2992

Traverse Gravel Terrain/Traverse Sand Terrain





PURCHASE LIST:


- [8] 1200 x 2400 x 15 mm OSB
- ☐ [33] 45 x 90 x 2400 in post
- □ 2 cubic meter construction sand or 2 metric ton of 3/8 pea gravel

CUT LIST:

- ☐ [6] 1100 x 2200 x 15 mm OSB (A)
- ☐ [2] 500 x 1100 x 15 mm OSB (B)
- ☐ [2] 490 x 850 x 980 x 15 mm OSB triangle (C)
- ☐ [16] 45 x 90 x 2400 mm Post (D)
- ☐ [8] 45 x 90 x 2150 mm Post <u>75°</u> Mitre cut sq. to long point (E)
- ☐ [4] 45 x 90 x 1750 mm Post (F)
- ☐ [2] 45 x 90 x 1100 mm Post (G)
- ☐ [16] 45 x 90 x 1010 mm Post (H)
- ☐ [4] 45 x 90 x 550 mm Post 15° Mitre cut sq. to long point (I)
- ☐ [4] 45 x 90 x 300 in Post (J)

PRINT LIST:


■ None



850 mm

Fabrication

- Lay out two post (D) from each other such that post are on edge. Attach post (H) to post (D). Attach (1) OSB panel (A) to frame as shown in **Figure A**. Repeat for 5 additional panels.
- Cut out <u>two</u> Triangles (C) as shown in Figure B.
- Fabricate deck as shown In Figure C/D.
 Repeat for one additional deck frame.
- Place trays as shown in Figure E. Place tray on top of ramp.
- Attach triangle (C) as shown in Figure E.
- · Fill with aggregate.






ASTM International Committee on Homeland Security Applications; Response Robots (E54.09)



Negotiate



I do not have a good design for the apparatus. It uses the a regular wall bay.

Speak with Testu for materials

Fabrication
-

28



ASTM International Committee on Homeland Security Applications; Response Robots (E54.09)



Task Panel (22)

PURCHASE LIST:


- [2] 1200 x 2400 x 15 mm OSB
- [4] 50 x 90 x 2400 mm post
- [6] 90 x 90 x 2400 mm post
- [9] 50 ID mm x 2400 mm PVC Pipe
- [9] 40 ID mm x 2400 mm PVC Pipe
- [198] 50 mm PVC Caps (https://www.ferguson.com/product/proflo-dwv-heavy-duty-highpressure-pvc-cap-pftc/_/A-ProdFamily-115673)
- [198] 50 mm Threaded Plug (http://www.grainger.com/product/LASCO-Threaded-Plug-22FK11?functionCode=P2IDP2PCP)


CUT LIST:


- [22] 330 x 330 x 15 mm OSB (A)
- ☐ [22] 90 x 90 x 300 mm Post 45° Mitre cut long to long point (B)
- ☐ [44] 90 x 90 x 90 mm Post 45° Mitre cut sq. to long point (C)
- ☐ [44] 45 x 90 x 300 mm Post (D)
- ☐ [198] 50 ID mm x 100 mm PVC Pipe
- ☐ [198] 40 ID mm x 75 mm PVC Pipe

PRINT LIST:

Random Lines.pdf








Top View

12.5 mm FIGURE B







Fabrication

Attach angled posts (B and C) together as shown in Figure A.

[1] Blue duct tape

□ [1] Red/Black Markers

[1] Velcro

- Attach caps as shown in Figure B.
- Attach post (D) to backside of OSB Panel (A) as shown in **Figure B**. Note: the 12.5 mm offset from edge.
- Attach pre-printed lines to the inside surface of the pipes. Lines are bottom justified. Number of lines should be between 2-6 and spaced randomly.
- Attach pipes to caps.
- Wrap top of 50 mm pipe with blue tape as shown in Figure C
- Mark top of treaded plug as shown in Figure C.
- Insert 40 mm pipe into the threaded plug. Wrap 25 mm Velcro at the end of the pipe as shown in Figure C.






ASTM International Committee on Homeland Security Applications; Response Robots (E54.09)



Dexterity




PURCHASE LIST:

- ☐ [7] 1200 x 2400 x 15 mm OSB
- ☐ [3] 90 x 90 x 2400 mm Post
- ☐ [7] 45 x 90 x 2400 mm Post
- ☐ [8] 330 x 330 x 300 in crate
 (https://www.uline.com/Product/ProductDetailRootItem?modeInumber=S-16317)

CUT LIST:

- ☐ [12] 550 x 565 x 19 mm OSB (A)
- ☐ [12] 140 x 550 x 19 mm OSB (B)
- ☐ [24] 140 x 530 x 19 mm OSB triangle (C)
- ☐ [24] 90 x 90 x 140 mm Post (D) 15° Mitre cut sq. to long point
- ☐ [24] 90 x 90 x 60 mm Post (E) 15° Mitre cut sq. to long point
- ☐ [4] 45 x 90 x 2355 mm Post (G)



G G G G G 2355 mm

Fabrication


- Place triangles (C) flatly on the floor. Attach one top post (E) to support triangle (F) and repeat for additional side as shown in Figure A. Note: Posts will be flush with the top of support triangle (C).
- Attach Front Leg (F) as shown in **Figure A**.
- Attach ramp surface (A) to support triangles (C). Note: **Use rougher side up as the ramp surface if there is a difference in surface texture.**
- Attach back plate (B) to high side of ramp as shown in Figure A.
- Attach post (G) to panel F as shown in Figure B.
- Crates are screwed to the containment border.

FIGURE B

ASTM International Committee on Homeland Security Applications; Response Robots (E54.09)



Dexterity Unit




PURCHASE LIST:

- [3] 1200 x 2400 x 15 mm OSB
- [9] 45 x 90 x 2400 mm Post

CUT LIST:

- ☐ [2] 1200 x 1200 x 11mm OSB (A)
- ☐ [1] 1140 X 1200 X 11 mm OSB (B)
- ☐ [3] 1100 x 1200 x 11 mm OSB (C)
- ☐ [1] 45 x 90 x 1490 mm Post 45° Mitre cut long pt. to long pt. (D)
- ☐ [12] 45 x 90 x 1200 mm Post (E)
- ☐ [1] 45 x 90 x 1110 mm Post (F)
- ☐ [1] 45 x 90 x 1055 mm Post (G)
- [4] 45 x 90 x 370 mm Post (H)



Fabrication

Shelf


- Attach posts (E) to Panel (C) as shown in Figure A.
- Attach 2nd panel (C) to complete shelf.


Container

- Attach posts (E) to Panel (A) as shown in Figure B. Repeat for other side panel.
- Attach back panel (B) to panels (A) as shown in Figure
- Attach post F to bottom as shown in Figure B

Flooring

- Attach posts E and G to panel C as shown in Figure C.
- Attach post D to panel C as shown in Figure C.
- Attach post H to panel C as shown in Figure C.







ASTM International Committee on Homeland Security Applications; Response Robots (E54.09)



Additional Under/Over Shelf (6)






PURCHASE LIST:

- [6] 1200 x 2400 x 15 mm OSB
- [15] 45 x 90 x 2400 mm Post

CUT LIST:

- ☐ [12] 1100 x 1200 x 11 mm OSB (A)
- [30] 45 x 90 x 1200 mm Post (B)



Fabrication

Shelf


- Attach posts (B) to Panel (A) as shown in Figure A.
- Attach 2nd panel (A) to complete shelf. Repeat for 5 additional shelves.

FIGURE A - Shelf

ASTM International Committee on Homeland Security Applications; Response Robots (E54.09)



Block Wall



PURCHASE LIST:

- ☐ [1] 1200 x 2400 x 15 mm OSB
- ☐ [4] 45 x 90 x 2400 mm Post

CUT LIST:

- ☐ [1] 1200 x 1200 x 11 mm OSB (A)
- ☐ [1] 45 x 90 x 1200 mm Post (B)
- [2] 45 x 90 x 150 mm (C) 15° Bevel cut lonsq pt. to long pt.
- □ [20] 45 x 90 x 300 mm (D)





FIGURE A



Fabrication


- Attach board B and C to board A as shown in Figure A.
- Attach board D to board D as shown in Figure B. Repeat for 9 additional pairs



ASTM International Committee on Homeland Security Applications; Response Robots (E54.09)



Shoring




PURCHASE LIST:

- ☐ [1] 1200 x 2400 x 15 mm OSB
- ☐ [2] 90 x 90 x 2400 mm Post
- ☐ [1] 45 x 90 x 2400 Post
- ☐ [1] 50 ID mm x 1200 mm Pipe
- ☐ [1] 50 mm Cap

CUT LIST:

- ☐ [1] 1200 x 1200 x 11 mm OSB (A)
- ☐ [12] 90 x 90 x 300 mm Post (B)
- ☐ [1[45 x 90 x 300 (C)



Fabrication

- Attach board B and C on panel A as shown in Figure A.
- Attach pipe cap to board C
- Insert pipe
- Additional 10 boards (B) are used during the task.

FIGURE A

ASTM International Committee on Homeland Security Applications; Response Robots (E54.09)



NOTE:

OSB underlayment to cover the floor is not calculated.

This will need to be calculated.

ASTM International Committee on Homeland Security Applications; Response Robots (E54.09)




Tools and Admin Section



Standard Test Methods for Ground SystemsASTM International Committee on Homeland Security Applications; Response Robots (E54.09)





- ☐ (1) Dispatch board
- (100+) Magnets



(1) HDMI Computer Monitor >21 in



(20) Clipboards



Standard Test Methods for Ground SystemsASTM International Committee on Homeland Security Applications; Response Robots (E54.09)



Ver. 2018 A











- ☐ (30) -Gloves
- ☐ (5) Safety Glasses
- ☐ (2) Ear Muff
- ☐ (10) Clip on nail pouch
- ☐ (1) First Aid Kit

ASTM International Committee on Homeland Security Applications; Response Robots (E54.09)







□ Fire extinguishers/sand buckets/ etc... should be stationed at the operator stations, team paddock and battery charging stations.



☐ (32) - Rigid Milk Crates




(1) Shipping Scale 440 LB/200 KG Capacity



ASTM International Committee on Homeland Security Applications; Response Robots (E54.09)







[4] Cordless drills

[6] Battery chargers

☐ [12] Total batteries



☐ [2] Corded drill

☐ [1] Circular Saw

☐ [1] Miter Saw



■ Drill sets

Typical size drill bits

Nut drivers

Torx/Star bit sets

☐ Screw Driver bits



☐ Paddle Bit Set

☐ [3] 1- 4cm (1/2 - 1.5 in)



ASTM International Committee on Homeland Security Applications; Response Robots (E54.09)





☐ Hole saw

☐ [3] 15 cm (6 in) diameter

☐ [3] 5 cm (2 in) diameter



Tape Measure

☐ [2] 30m/100ft tape measure

☐ [4] 8m/25ft tape measure



Cable Ties

☐ [200] Various sizes

☐ [5] Cable tie cutters



Duct tape

☐ [5] Rolls of Safety Yellow duct tape

☐ [5] Rolls of Safety Orange duct tape

☐ [5] Rolls of Safety Red duct tape

☐ [5] Rolls of Blue duct tape

☐ [5] Rolls of Black /Yellow diagonal stripe tape



ASTM International Committee on Homeland Security Applications; Response Robots (E54.09)





1/4in x 4in

1/4in x 2-1/2in

1/4in x 1-1/2in

1/4in x 1in

Star/Torx bit screws with washer heads

- ☐ [500] 12 mm (1 in) long
- ☐ [1000] 40 mm (1 1/2 in) long
- ☐ [2000] 60 mm (2 ½ in) long
- □ [500] 120 mm (4 in) long
- ☐ [50] Matching star/torx bits for each size



Hardware

- ☐ [8] Hinges 100 mm (4 in)
- ☐ [200] washers 25 mm (1 in)



☐ [10] Power cords

☐ [30] Power Strips





ASTM International Committee on Homeland Security Applications; Response Robots (E54.09)



☐ Color printer and copier with supplies

[1] Color inkjet printer/copier

□ USB and power cables

□ Printer driver software

☐ [4] Spare paper packs


☐ [4] Spare ink colors and black



☐ Briefing/planning/task list support

☐ [3] Dry erase whiteboards

☐ [3] Sets of markers/erasers



☐ [2] Stapler, staples

☐ [4] scissors

☐ [1] Scotch (clear) tape

☐ [50] Pencils

☐ [100] paper clips

☐ [10] Black permanent Sharpie Markers-large

☐ Various sizes binder clips





ASTM International Committee on Homeland Security Applications; Response Robots (E54.09)





AV equipment

- [3] Large LCD display
- [2-3] Pan Security Camera with cable
- Ability to switch between the cameras
- PA system



ASTM International Committee on Homeland Security Applications; Response Robots (E54.09)



Additional Materials Needed

ASTM International Committee on Homeland Security Applications; Response Robots (E54.09)





OSB Plywood surface

NOTE:

OSB underlayment to cover the floor is not calculated. This will need to be calculated.

Additional lumber:

[5] sheets of 19mm OSB plywood

[10] sheets of 15mm OSB plywood

[20] 45 x 90 x 2400 mm post

[10] 90 x 90 x 2400 mm post



Standard Test Methods for Ground SystemsASTM International Committee on Homeland Security Applications; Response Robots (E54.09)



~140mm

[300] 140 x 400 mm (6 in) concrete block ~400mm

Page 47